

Pro 10 Series Printers

DURA-ID SOLUTIONS

Continuous Media Four & Five Colour Label Printing

The heavy duty die-cast aluminium design makes this series of printers ideal for industrial environments with a print speed of up to 8" per second.

Applications include:

- Industrial Duty Printing
- Healthcare Patient Safety
- Pharmaceutical
- Horticultural Self-Adhesive Labels
- Chemical Bottle Labelling
- Work in Process
- Order Fulfilment
- Distribution
- Shipping/Receiving



Speak to our experts to discuss your requirements today.

+44 (0) 114 242 2111

info@dura-id.com

Key Features

- Easily set up your production line ready for your labels to go on an applicator
- Continuous media printer with the ability to utilise a built-in guillotine
- Range of materials are available from economy through to premium
- Built for speed and durability
- 5" maximum media width



Product Specifications

Printer Model	Pro 10 Series
Colour Options	Pro1040 (CMYK) & Pro1050 (CMYK + W)
Media Type	Plain Paper, Film, Plain Paper Label, Glossy Paper Label, Synthetic Film Label
Media Width	Roll Paper: 25.4mm (1.0") - 130mm (5.1") including liner
Media Thickness	0.076 - 0.250mm
Label Length	12.7mm (0.5") - 1320.8mm (52")
Label Width	25.40 - 125.76mm
Media Detection	Black Mark (printed on back of liner), Gap, None
Media Format	Roll
Roll Outer Diameter / Core Inner Diameter	Max. Φ 203.2mm (Φ 8") / Φ 76.2mm (Φ 3")
Roll Wind Direction	Face-out, Face-in
Minimum Print Margin	Top: 2.12mm, Bottom: 2.12mm, Right: 2.12mm, Left: 2.12mm
Print Position Accuracy / Cut Accuracy	Vertical: \pm 0.5mm, Horizontal: \pm 0.5mm / Vertical: \pm 0.5mm
Cutable Media Length	Min. 101.6mm
Print Resolution	1200 x 1200 dpi, 600 x 600 dpi
Print Speed	Max. 152.4mm/s (6ips)
Interface	1000BASE-T/100BASE-T/10BASE-T, USB2.0 (High Speed), TCP/IP, IPX/SPX, EtherTalk
Protocol	TCP/IP, IPX/SPX, EtherTalk
Printer Language	Adobe PostScript3, PCL 5c emulation, PCL 6 (XL) emulation
Supported OS	Windows 10, Windows Server 2012 R2, Windows Server 2012, Windows Server 2008 R2, Windows Server 2008, Windows Server 2008 x64, Windows 10 x64, OS X 10.10, Windows 8.1, Windows 8.1 x64, OS X 10.11, Windows Server 2016, macOS 10.12, Windows 8, Windows 8 x64, Windows 7, Windows 7 x64
Processor Speed	ARM 1.2 GHZ
Memory (std./max)	2,000 MB
Hard Disk Drive	250 GB
Font	Adobe PostScript 136 fonts, PCL emulation 81 scalable fonts, 4 bitmap fonts
Auto Cutter	Rotary blade full cut
Dimensions (W x D x H)	1,049 x 341 x 451 mm (printer with unwinder)
Weight (includes supplies)	Approx. 60.0 kg (printer with unwinder)
Operating Environment	Operating: 10 - 30 °C, 20 - 70 %RH, Storage: -10 - 43 °C, 10 - 90 %RH, No condensation
Power Source	Single phase 230V AC +/-10%, 50/60 Hz +/-2%
Power Consumption	Operating: Max. 1,200W/Ave. 710W, Idle:27W w/o rewriter, Power Save: 25W
Safety & Environment	RoHS, Network Access License, cUL Mark, cULus Mark, GS Mark, UL Mark, CSA Mark, EMC-Directive, CE Mark, GS Mark
Transfer Belt / Fuser Life	150K Pages (approx. 22km of labels @ A6 size)
Waste Toner Box Life	50k Pages
In the Box	Manuals, Power cable (UK & EUR), DVD-ROM (Software Drivers & BarTender® UltraLite)
Accessories	Rewriter with matrix removal, bench & bench with extension