

Zebra 220Xi4 Printer

Industrial Thermal Transfer Printer

The Xi Series printer are known for their durability, consistent print quality, fast printing speed, longevity and reliability in demanding applications.

The all metal construction makes it the ideal printing solution for harsh environments.

Applications Include:

- Chemical Labels
- Inventory Labels
- Pallet Labels
- Work-In-Progress
- Product ID / Serial numbers
- Package Labelling
- Small Item Labelling
- Shipping / Receiving

DURA-ID

SOLUTIONS



Speak to our experts to discuss your requirements today.

+44 (0) 114 242 2111

info@dura-id.com



Key Features

- Clear side doors allows easy monitoring of consumables
- 8.5" maximum print width
- Maximum print speeds up to 10" per second
- Zebra OneCare for repairs
- 600 dpi print resolution version available
- Prints labels as small as 1/8" (3mm)
- Handles a variety of media (from paper to tag stocks)

Product Specifications

	110Xi4	140Xi4	170Xi4	220Xi4
Resolution	203 dpi/8 dots per mm 300 dpi/12 dots per mm 600 dpi/23.5 dots per mm (110Xi4 only)			
Memory	64 MB Flash; 16 MB RAM			
Maximum print width	4.0"/102 mm	5.04"/128 mm	6.6"/168 mm	8.5"/216 mm
Maximum print speed	14"/355.6 mm per second (203 dpi) 12"/304.8 mm per second (300 dpi) 6"/152.4 mm per second (600 dpi)	14"/355.6 mm per second (203 dpi)	12"/304.8 mm per second (203 dpi) 8"/203.2 mm per second (300 dpi)	10"/254 mm per second (203 dpi) 6"/152.4 mm per second (300 dpi)
Media sensors	Transmissive and reflective			
Media Characteristics				
Media width	0.79"(20mm) to 4.5" (114 mm)	1.57" (40 mm) to 5.51" (140 mm)	2.0" (51 mm) to 7.1" (180 mm)	4.25" (108 mm) to 8.8" (224 mm)
Maximum media roll size	8.0" (203 mm) outside diameter on a 3" (76 mm) inside diameter core			
Thickness	0.003"/0.076 mm to 0.012"/0.305 mm			
Media types	Continuous, die-cut gap, black mark, notch or hole			
Minimum non-continuous label length	0.25"/6 mm (Rewind mode) 0.5"/13 mm (Peel mode) 0.7"/18 mm (Tear-off mode) 1.5"/38 mm (Cutter mode)			
Ribbon Characteristics				
Outside diameter	3.2"/81.3 mm			
Standard length	1476'/450 M 984'/300 M			
Width	0.79" (20 mm) to 4.33" (110 mm)	1.57" (40 mm) to 5.1" (130 mm)	2.0" (51 mm) to 6.7" (170 mm)	4.25" (108 mm) to 8.6" (220 mm)
Core I.D.	1.0"/25.4 mm			
Operating Characteristics				
Environmental	Operating Temperature: 40°F to 105°F/5°C to 40°C • Thermal transfer: 40°F to 105°F/5°C to 40°C • Direct thermal: 32°F to 105°F/0°C to 40°C Operating Humidity: 20% to 85% non-condensing Storage/Transportation Temperature: -40°F to 140°F/ -40°C to 60°C Storage Humidity: 5% to 85% non-condensing			
Electrical	90-264VAC; 48-62Hz ENERGY STAR qualified (140Xi4, 170Xi4, 220Xi4)			
Agency Approvals	IEC 60950-1, EN 55022 Class B, EN 55024, EN 61000-3-2, EN 61000-3-3 Product Markings: cTUVus, CE, FCC-B, ICES-003, VCCI, C-Tick, NOM, S-Mark(Arg), CCC, GOST-R, BSMI, KCC, STB, and UkrSEPRO			
Physical Characteristics				
Height	15.5" / 393.7 mm			
Width	10.31" / 261.9 mm	11.31" / 287.3 mm	13.31" / 338.1 mm	15.81" / 401.6 mm
Depth	20.38" / 517.5 mm			
Weight	50 lbs. / 22.7 kg	55 lbs. / 25.0 kg	67 lbs. / 30.5 kg	72 lbs. / 32.7 kg