

(High Tack) Gloss PP Self-Adhesive Product Specification



Product Description and Applications

Gloss PP Self-Adhesive is ideal for use in environments where durability is essential due to the high tack adhesive on the reverse of the label. Gloss PP S/A is resistant to water, various chemicals and most household detergents. A key application for this product would include labelling an uneven surface that required durability from chemicals or long-term outdoor exposure.

Industries that currently utilise Gloss PP S/A include:

Medical
Steel & Metals
Horticulture

Chemicals
Construction
Engineering

Printability

Gloss PP Self-Adhesive is ideal for use with a thermal transfer printer and suitable ribbon where variable information needs to be included on a pre-printed or plain label. Pre-printable in up to 6 colours.

Storage Guidelines

Dura-ID Solutions recommend keeping this product out of direct sunlight in temperatures between 20°C - 25°C at 40-50% humidity. Prolonged storage at higher or lower temperatures may affect the shelf-life of this product.

Recyclability

Gloss PP Self-Adhesive is a polypropylene film and therefore recyclable under Class 5.



Thickness	µm - 60 +/- 5%
Material Weight	GSM - 45 +/- 5%
Adhesive Coat Weight	GSM - 40 +/- 5%
Application Temperature	0°C
Service Temperature	-20°C to +50°C
Recommended Ribbon	Dura-ID Premium

The above values and information are given in good faith but without warranty. Dura-ID recommends the testing of samples to ascertain suitability. It is the responsibility of the end user to satisfy the suitability of the product for the application. All goods are supplied in accordance with our standard conditions of sale.

Dura-ID Solutions Limited

Sheffield Office: +44 (0) 114 242 2111

Devon Office: +44 (0) 1803 668 090

www.dura-id.com

info@dura-id.com

sales@dura-id.com



Certificate number: FM 690323