

Matt PP Self-Adhesive (BS5609)

Product Specification



Product Description and Applications

Matt PP Self-Adhesive (BS5609) is ideal for use in environments where high durability is required due to the high tack adhesive. Matt PP S/A (BS5609) is resistant to water, various chemicals and most household detergents. These properties make it a key label material for various industries where product identification needs to be maintained.

Industries that currently utilise Matt PP S/A (BS5609) include:

Chemicals
Steel & Metals
Horticulture

Brick & Block
Construction
Engineering

Printability

Matt PP Self-Adhesive (BS5609) is ideal for use with a thermal transfer printer and suitable ribbon where variable information needs to be included on a pre-printed or plain label. Pre-printable in up to 6 colours.

Storage Guidelines

Dura-ID Solutions recommend keeping this product out of direct sunlight in temperatures between 20°C - 25°C at 40-50% humidity. Prolonged storage at higher or lower temperatures may affect the shelf-life of this product.

Recyclability

The face material of Matt PP S/A (BS5609) is recyclable, however the adhesive backing is not.

Approvals

The material and adhesive of this product are Isega approved for direct contact with dry and non-fatty foods.

Thickness	µm - 75 +/- 10%
Material Weight	GSM - 63 +/- 10%
Adhesive Coat Weight	GSM - 40 +/- 5%
Application Temperature	0°C
Service Temperature	-20°C to +80°C
Recommended Ribbon	Dura-ID Standard

The above values and information are given in good faith but without warranty. Dura-ID recommends the testing of samples to ascertain suitability. It is the responsibility of the end user to satisfy the suitability of the product for the application. All goods are supplied in accordance with our standard conditions of sale.

Dura-ID Solutions Limited

Sheffield Office: +44 (0) 114 242 2111

Devon Office: +44 (0) 1803 668 090

www.dura-id.com

info@dura-id.com

sales@dura-id.com



Certificate number: FM 690323