

Product Specification



Matt-Tuff Self-Adhesive

Description

Matt-Tuff is a matt white coated HDPE film laminated to a white glassine liner with a very high tack & high coat weight BS5609 marine approved adhesive. The face is extremely print receptive to a variety of print methods. The adhesive is a rubber based hot melt designed to give superior initial tack on moist and rough surfaces. The properties of the face combined with the very aggressive adhesive result in the applied labels displaying tamper evident properties, making label removal and reapplying of the label very difficult. The material & adhesive is Isega approved for direct contact with dry and non-fatty foods.

Printability

Variable information printing including barcodes is possible using a combination of thermal transfer printers and suitable ribbons. Dura-ID are happy to advise on the best printer and ribbon solution combinations for maximum resistance and readability.

Applications

Matt-Tuff is ideally suited to applications where label durability is required, surviving long term outdoor exposure and resisting water and various chemicals to ensure product identification is maintained. These properties are particularly relevant to the Chemical, Steel, Building & Construction and Horticultural industries.

Thickness	Micron - 100 +/- 10%
Weight	GSM - 85 +/- 8%
Temperature Resistance	-20°C - +80°C
Adhesive Strength	Marine Approved Permanent
Recommended Ribbon	Dura-ID Standard

The above values and information are given in good faith but without warranty. Dura-ID recommends the testing of samples to ascertain suitability. It is the responsibility of the end user to satisfy the suitability of the product for the application. All goods are supplied in accordance with our standard conditions of sale.

